

## Rfid Access Card Reader For Access Control System Kits



KR602

### Introduction

KR602E: 125KHz Proximity card reader

KR602M: 13.56MHz Mifare card reader

### Features

- > 125KHz Proximity /13.56MHz mifare Card Reader
- > Read Range: Up to 10CM(125KHz)/5CM(13.56MHz)
- > 26/34bit Wiegand (default)
- > Easy to install on Metal Door Frame or Mullion
- > External LED Control
- > External Buzzer Control
- > Indoor / Outdoor Operation
- > Solid Epoxy Potted
- > Waterproof IP65
- > Reverse Polarity Protection

### Specifications

<b>Read Range</b>	KR602EM: Up to 10CM	<b>Operating Temperature</b>	-20° to +65°C
	KR602MF:Up to 5CM	<b>Operating Humidity</b>	10% to 90% relative humidity non-condensing
<b>Reading Time (Card)</b>	<=300ms	<b>Colour</b>	Black
<b>Power / Current</b>	DC 6-14V / Max.70mA	<b>Material</b>	ABS+PC with texture
<b>Input Port</b>	2ea	<b>Dimension(W x H x T)mm</b>	86X86X20mm
<b>Output Format</b>	26bit/34bit Wiegand (default)	<b>Weight</b>	50g
<b>LED Indicator</b>	2 Colour LED Indicators(Red and Green)	<b>Index of Protection</b>	IP65

