



iFace 307

Dynamic Face Access Controller

Specifications

CPU processor	Dual-core processor A7-1.2GHZ
Operating system	LINUX
Memory	256MB
Storage	8GB
Camera	Double pole 1MP
User capacity	10,000
Face capacity	10,000
IC ID card	10,000
Logs record	200,000
Verifying method	Face/Fingerprint/Card
Verifying speed	≤0.3S
LCD Display	5 inches IPS HD display(720*1280)
Touch display type	Capacitive touch screen
Communication	USB 2.0,U disk,10M/100M Adaptive/WIFI
Language	English
Output	Wiegand26 34 / RS485 / Magnetic contact / Electric lock / Exit button / Alarm / Door bell
Power Supply	DC12V/2A
Reading Distance	0.5~2M(0.5-1M Living distance)
Working temperature	-30°C~60°C

Working humidity	0%~90%
Antistatic	Touching $\geq 4KV$ Air $\geq 8KV$
Special features	Binocular biopsy
Using environment	Indoors
Dimensions	200x85x24mm

Dimensions(mm)



S4A Industrial Co.,Limited

Address: The 2nd floor, Jinmin'an Industrial Zone, #529, Bulong Rd.
Bantian St. Longgang Dist. Shenzhen, PRC.. CN 518131

Tel: +86 755 29450011

www.s4a-access.com / Email: sales@s4a-access.com
Mob/Whatsapp/Wechat/Viber: +86 134 1050 0721